

## DS-KM8301


## Video Intercom Master Station

### Key Features

- Glass panel and aluminum-alloy bracket
- Supports video intercom
- Supports live view of door stations and IP camera
- Noise suppression and echo cancellation
- Alarm processing function
- Supports remote unlocking door function
- Supports hands-free mode
- Supports video intercom between master stations
- (Optional) Suitable for wall mounting




### Typical Application



## Specifications

<b>Model</b>		<b>DS-KM8301</b>
<b>System parameters</b>	<b>Processor</b>	High-Performance Embedded SOC Processor
	<b>Operation system</b>	Embedded Linux Operation System
<b>Video parameters</b>	<b>Camera</b>	CMOS 0.3 MP
	<b>Video compression standard</b>	H.264
	<b>Resolution</b>	1280 x 720, 704 x 576
	<b>Video frame rate</b>	25 fps, 12.5 fps
<b>Display parameters</b>	<b>Display screen</b>	7-Inch Colorful TFT LCD
	<b>Display resolution</b>	1024 × 600
	<b>Operation method</b>	Capacitive Touch Screen, Touch Key, Physical Button
	<b>Operation interface</b>	Flattened UI Operation Interface
<b>Audio parameters</b>	<b>Audio input</b>	Built-in Omnidirectional Microphone + External Handset
	<b>Audio output</b>	Built-in Loudspeaker + External Handset
	<b>Audio compression standard</b>	G.711 U
	<b>Audio compression rate</b>	64 Kbps
	<b>Audio quality</b>	Noise Suppression and Echo Cancellation
<b>Network parameters</b>	<b>Ethernet</b>	10/100/1000 Mbps Self-Adaptive Ethernet
	<b>Network protocol</b>	TCP/IP, RTSP
<b>Device interfaces</b>	<b>Network interface</b>	1 RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
	<b>RS-485</b>	2 RS-485 Half-Duplex Port
	<b>USB</b>	1 USB Interface for Inserting U-Disk
	<b>I/O input</b>	4 On-Off Input
	<b>I/O output</b>	2 On-Off Output, 2 Relay Output
<b>General</b>	<b>Material</b>	Plastic
	<b>Power supply</b>	12 VDC
	<b>Power consumption</b>	≤10 W
	<b>Working temperature</b>	-10° C to + 55° C (14° F to 131° F)
	<b>Working humidity</b>	10% to 90%
	<b>Dimensions (L × W × H)</b>	436 mm × 215 mm × 67 mm (17.2" × 8.5" × 2.6")
	<b>Certification</b>	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE

## Appearance and Interfaces



Index	Description	Index	Description
1	Phone	9	Accept/Decline Button
2	Built-in Camera	10	Unlock Button
3	LCD Display Screen	11	Speaker Button
4	Dial Keypad	12	12 VDC Power Supply
5	Information Indicator	13	Terminals
6	Alarm Indicator	14	USB Interface
7	Alarm Indicator	15	Network Interface
8	Microphone		

Distributed by

## Available Model

DS-KM8301

## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-42-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com