


LDH49-EAO400K

49" Outdoor Wall-mounted Digital Signage



Features:

- Industrial design, waterproof galvanized steel housing, tempered protective glass.
- High brightness and anti-reflection glass ensure excellent visibility under direct sunlight.
- Dahua MPS platform provides unified remote management for system integrators and media operators.
- Strong 4 core processor provides powerful decoding capabilities, enabling premium display performance.
- Built-in media player software and USB player provide multiple methods to play contents.



Technical Specification

Display

Model	LDH49-EAO400K
Backlight	LED
Screen Size	49"
Aspect Ratio	16:9
Resolution	3840x2160
Display Colors	16.7M
Brightness	2500nits
Contrast Ratio	1200:1
Viewing Angle(HxV)	178°/178°
Display Mode	Horizontal
Response Time	8ms
Lifespan	50,000h

Connectivity

Input	RJ45 x1, USB x2, TF Slot x1, HDMI x1, Audio Inx1
External Control	IR, RJ45(LAN), USB
Wi-Fi	Optional
Speaker	5Wx2
Smart Signage Platform	Media Publish System 3.0

Touch	Not Support
-------	-------------

Power & Environmental Conditions

Power Supply	AC100-240V, 50/60Hz
Consumption	250W
Operating Temperature	-15°C~+45°C (5°F~113°F)
Operating Humidity	5%~90%
Protection Level	IP55 (IP65 customized)
Cooling Method	Air-cooled(default) Air conditioning(customized)

Mechanical Specification

Dimensions	1314x844x150mm
Package	1460x1084x380mm
Net Weight	102kg
Gross Weight	118kg

Internal Player

Processor	Quad-core Cortex-A17 up to 1.6GHz
Operating System	Android 8.1
RAM	2GB
Storage	16GB
Material Type	Video, audio, image, time, weather, countdown, txt, web page, stream media, pdf
Video	mp4,avi,mov,asf,wmv,rm,rmbv,mkv A single file can upload up to 2G, and the resolution cannot exceed 4K
Audio	mp3,wma,wav A single file can upload up to 500M
Image	jpg,jpeg,gif,bmp,png A single file can upload up to 30M, and the resolution cannot exceed 4K
Documents	pdf, doc, docx, ppt, pptx, xls, xlsx and txt. A single file can upload up to 200 MB
Decoding Capacity	1ch@4K or 4ch@1080P

Dimensions(mm)
